
Trimming the Points of Half-Square Triangles: "A" Trims Using a Regular Ruler

Method: Align the 2 short sides of a triangle patch with both lengthwise and crosswise rulings of the listed size* (the trim measurement). The points will extend 3%" beyond the ruler. Trim both points off along the ruler's edges.


Cut Size of Triangle	*Trim Size
1%"	1½"
21/8"	1¾"
23/8"	2"
2%"	2½"
3"	2%"
3%"	3½"
51%"	4¾"
6%"	6½"
8%"	8½"
93%"	9"



A 1) Align the vertical and horizontal rulings of the listed *trim size with the short sides of the triangular patch. Cut off the right tip along the edge of the ruler as shown at left.

A Trim: Step 1

A 2) Keeping the vertical and horizontal rulings aligned, cut off the tip along the top edge of the ruler as shown at right.




A Trim: Step 2

Trimming the Points of Quarter-Square Triangles: "B" Trims Using a Regular Ruler

Method: Align the the long side of a fabric triangle patch with the bottom lengthwise ruling on your rotary ruler. Also align the corner of the triangle patch with the vertical ruling of the listed size* (the midline ruling). One point will extend ¾" beyond the ruler. Trim the point off along the ruler's edges. Turn the patch face down and trim off the other point in the same manner.

Cut Size of Triangle	*Midline Ruling
31/4"	11/4"
3¾"	1½"
41/4"	1¾"
51/4"	21/4"
71/4"	31/4"
934"	4½"



B Trim: Step 1

B 1) With the fabric triangle face up, align the vertical *midline ruling with the square corner of the triangle. Align the bottom of the patch with the bottom line of the ruler. Cut as shown.

